



PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

#5  
266/31301  
RECEIVED  
FEB 21 2001  
IC 2600 MAILROOM

In re application of

Bart Gerard PAUWELS

Attorney Docket Q61979

Appln. No.: 09/732,748

Group Art Unit: 2661

Confirmation No.: 2824

Examiner: Not yet assigned

Filed: December 11, 2000

For: METHOD FOR CHECKING THE TRANSFER OF DATA CELLS IN AN  
ASYNCHRONOUS SWITCHING ARRANGEMENT, ELEMENTARY SWITCHING  
UNIT AND NETWORK EQUIPPED FOR SUCH A METHOD


**SUBMISSION OF PRIORITY DOCUMENT**

Commissioner for Patents  
Washington, D.C. 20231

Sir:

Submitted herewith is a certified copy of the priority document on which a claim to  
priority was made under 35 U.S.C. § 119. The Examiner is respectfully requested to  
acknowledge receipt of said priority document.

Respectfully submitted,

  
David J. Cushing  
Registration No. 28,703

SUGHRUE, MION, ZINN,  
MACPEAK & SEAS, PLLC  
2100 Pennsylvania Avenue, N.W.  
Washington, D.C. 20037-3213  
Telephone: (202) 293-7060  
Facsimile: (202) 293-7860

Enclosures: **CERTIFIED COPY OF EUROPEAN APPLICATION NO. 99403179.7**

Date: February 16, 2001

**THIS PAGE BLANK (USPTO)**



Europäisches  
Patentamt

European  
Patent Office

Office européen  
des brevets

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-  
gen stimmen mit der  
ursprünglich eingereichten  
Fassung der auf dem näch-  
sten Blatt bezeichneten  
europäischen Patentanmel-  
dung überein.

The attached documents  
are exact copies of the  
European patent application  
described on the following  
page, as originally filed.

Les documents fixés à  
cette attestation sont  
conformes à la version  
initialement déposée de  
la demande de brevet  
européen spécifiée à la  
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

99403179.7

**CERTIFIED COPY OF  
PRIORITY DOCUMENT**

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

I.L.C. HATTEN-HECKMAN

DEN HAAG, DEN  
THE HAGUE,  
LA HAYE, LE

11/12/00

09/732,748  
Q61979



16/1 RECEIVED  
FEB 21 2001  
TC 2600 MAILROOM

**THIS PAGE BLANK (USPTO)**

**THIS PAGE BLANK (USPTO)**



Europäisches  
Patentamt

European  
Patent Office

Office européen  
des brevets

**Blatt 2 der Bescheinigung**  
**Sheet 2 of the certificate**  
**Page 2 de l'attestation**

Anmeldung Nr.:  
Application no.: 99403179.7  
Demande n°:

Anmeldetag:  
Date of filing: 16/12/99  
Date de dépôt:

Anmelder:  
Applicant(s):  
Demandeur(s):  
ALCATEL  
75008 Paris  
FRANCE

Bezeichnung der Erfindung:  
Title of the invention:  
Titre de l'invention:

Method for checking the transfer of data cells in an asynchronous switching arrangement

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:  
State:  
Pays:

Tag:  
Date:  
Date:

Aktenzeichen:  
File no.  
Numéro de dépôt:

Internationale Patentklassifikation:  
International Patent classification:  
Classification internationale des brevets:

H04L12/56

Am Anmeldetag benannte Vertragsstaaten:  
Contracting states designated at date of filing: AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE/TR  
Etats contractants désignés lors du dépôt:

Bemerkungen:  
Remarks:  
Remarques:

See for title page 1 of the description.

**THIS PAGE BLANK (USPTO)**

- 1 -

**METHOD FOR CHECKING THE TRANSFER OF DATA CELLS IN  
AN ASYNCHRONOUS SWITCHING ARRANGEMENT, ELEMENTARY  
SWITCHING UNIT AND NETWORK EQUIPPED FOR SUCH A METHOD**

5           The present invention relates to a method for checking the transfer of data cells in an asynchronous switching arrangement and more specifically for detecting transfer errors of data cells due to unacceptable delays and unwanted copying. It also relates to switching units equipped for such a check.

10           Information transfer in an asynchronous switching network by means of data cells is disturbed when excessive delays or losses of data cells happen, such drawbacks being linked for instance to internal queuing for a switching unit in a switching arrangement.

15           Occurrence of such unacceptable delays at the level of a switching arrangement, for instance in an elementary switching unit, for the smallest or in a switching network for the biggest, is usually checked by measurements carried out at the edges of the switching arrangement. Localization of a faulty element, for instance a faulty buffer or a faulty switching device requires generation of dedicated test traffic and corresponding measurements. Use of dedicated test traffic connections is known for connection oriented switches, putting out of  
20   service a part of a switch is usually carried out with multi-path switches. All this usually requires specialized technicians with appropriate testing equipment and is sometimes long and costly, for instance when there are sporadic, pattern related malfunctions which are hard to reproduce on will, and consequently to localize.

25           Accordingly and as much as possible, test traffic for a detection in a large switching arrangement is usually limited in time and/or to a part fraction of the traffic which is transferred, for instance less than 1% of the total traffic. Obtention of a global detection picture, if possible, and localization of a faulty element are rather long tasks and accordingly they are not as efficient as needed.

30           An object of this invention, therefore, is to provide a method for checking the transfer of data cells in an asynchronous switching arrangement.

- 2 -

According to the invention, the method comprises a marking and a counting of the cells received and a counting of the cells, after switching when outputted from the switching structure of the arrangement, in order to verify that the counts correspond and to find transfer errors of data cells due to unacceptable delays and unwanted copying in the switching structure, said marking and said counting being obtained according to a periodical time frame made of interleaved checking cycles which are grouped by limited and successive series of a same determined number of cycles, each cycle including a first phase for marking and counting the cells as they are received, the identification mark, introduced in every cell received during this first phase, being related to the position of the cycle among the other cycles of the same series, with each first phase of a cycle following immediately the first phase of the preceding cycle, a second phase, overlapping with the first phase, starting with a determined delay which may be zero, after the beginning of the first phase of the same cycle and during this first phase, for a determined duration and for counting the cells, as soon as switched, which contain the identification mark introduced during the first phase of the same checking cycle, a determination being made at the end of the second phase of each checking cycle of the correspondence between the two counts obtained during the cycle, with a specific signaling as soon as the correspondence as otherwise determined for a cycle is not obtained.

Another object of this invention is to provide an elementary asynchronous switching unit including at least one asynchronous switching arrangement provided with means for checking the transfer of data cells in this elementary unit as recited in claim 4.

Another object of the invention is to provide an asynchronous switching network or sub-network including inter-linked switching units in one or several asynchronous switching arrangement(s), with each arrangement provided with means for checking the transfer of data cells in this elementary unit as recited in claim 5.

It should be noticed that the term 'comprising', used in the claims, should not be interpreted as being limitative to the means listed thereafter. Thus,



- 3 -

the scope of the expression 'a device comprising A and B' should not be limited to devices consisting only of components A and B. It means that with respect to the present invention, the only relevant components of the device are A and B.

These and other objects, advantages and features of the invention will  
5 become apparent from the following description thereof taken in conjunction with the accompanying drawings, which illustrate a specific embodiment of the present invention :

Figure 1 is a schematic view of an asynchronous switching arrangement.

10 Figure 2 is a schematic diagram showing the interleaving of observation cycles including two overlapping phases for input counting and output counting, according to an example relating to the detection method according to the invention.

Figure 3 is a schematic diagram illustrating an example of input and  
15 output counts related to an observation cycle

It is considered here that an asynchronous switching arrangement, as illustrated on figure 1 corresponds to the schematic basis structure common to all asynchronous switching items, from the elementary asynchronous switching units to the asynchronous switching networks themselves. An elementary asynchronous  
20 switching unit corresponds to an asynchronous switching arrangement, a network comprises inter-linked switching units organized in several asynchronous switching arrangements.

A basic asynchronous switching arrangement 1, as shown on figure 1, comprises one or more data cell inputs I1 to In for incoming data cells  
25 transferred by data links in order to be switched in a switching structure 2 for further transfer according to the needs of the switching network users, along transfer paths which are then available through this network for proper transfer to each recipient. It also comprises one or more data cell outputs O1 to Om for the transfer of data cells by outgoing data links from the switching structure 2, as  
30 soon as switched.

- 4 -

As known, the organization of the switching structure 2 corresponds to the main difference existing between asynchronous switching items, as considered here.

5 Incoming cells are received by means of an input interface 3 before being switched, in order to be oriented as necessary for switching purposes, usually according to routing information included in their respective cell headers.

10 Outgoing cells are transferred, as soon as switched, which may consist of an integrity check, a routing and a queuing operation, from the switching structure to the outgoing links respectively connected to outputs O1, Om, by means of an output interface 4.

As already pointed out above, the switching structure 2 comprises at least one and often several cascaded switching units connected to the data cell inputs I1, In and to the data cell outputs O1, Om. The switching arrangement 1 and more specifically the switching structure 2 are controlled by means of a supervision arrangement 5. Such a supervision arrangement usually includes control-processing units and clock-processing units with eventually some of their respective components located in the switching structure itself.

20 As already known, the switching structure 2 is a buffered structure which includes queuing devices including memory buffers for organizing appropriately the internal data cell traffic. Each cell to be further communicated is temporarily stored in a switch memory buffer as soon as it arrives before being transferred and as long as it cannot be further transferred from this switch memory buffer due to traffic volume. Accordingly there are risks of excessive cell delays or even of cell losses related to malfunctions in the queuing organization and more particularly in the book keeping of cells in the queues of the switching structure.

However, as long as there is a transfer of cells provided from a switch memory buffer with a maximal time delay for every individual cell transfer, there is also a possibility of checking whether the cell is output as foreseen.

30 According to the invention, a repetitive checking is made at the level of a switching structure 2, regardless of its constitution, in order to know if its traffic

- 5 -

output corresponds to its traffic input, as otherwise determined, such a determination being usually obtained at the level of a supervision organization. For this purpose, cells are continuously and cyclically counted when arriving and when leaving a switching structure 2 by respective input counting means 6 and  
5 output counting means 7.

According to the invention, the incoming cells transferred to switching arrangement 1 are specifically marked, for identification purposes, as soon as they are received by marking means 8 located for instance in the input interface 3 together with the input counting means 6, in order to be counted according to  
10 their respective identification mark after switching, just before being further outputted from the switching arrangement.

For this purpose marking and counting at the level of an asynchronous arrangement are obtained according to a periodical time frame made of interleaved checking cycles, which are grouped by limited and  
15 successive series of a same determined number of identical cycles, for instance four cycles in each series. Each cycle, such as C1 on figure 2, is divided in two phases, a first phase IC1 for marking and counting the cells as soon as they are received and a second phase OC1 for counting the cells as soon as they are switched for further transfer outside of the switching arrangement. Each  
20 incoming cell receives an identification mark corresponding to the position of the cycle during which it is received among the other cycles of the same series, for instance a two bits indication corresponding to the rank of the cycle among four, when there are four cycles in each series. The means for marking will not be detailed here, as they are already known from the prior art.

25 According to the invention, the first phase of each cycle immediately follows the first phase of the preceding cycle of the same series or of the preceding series, such as first phase IC2 after first phase IC1, first phase IC3 after phase IC2 and second first phase IC1 after first phase IC4 on figure 2. Each second phase starts with a determined delay d1 after the beginning of the first  
30 phase of the same cycle and for a determined duration t2, with t1 being the duration chosen for every first cycle. Determined delay d1 is a fixed value chosen

- 6 -

smaller than or at most equal to the minimal duration required by switching structure 2 for the transfer of a cell. Duration  $t_2$  is a fixed value at least equal to the sum of delay  $d_1$  with the determined maximal duration requested for the transfer of a cell by the switching structure, knowing that  $t_1$  is necessarily chosen  
5 longer than  $d_1$ .

The cells received by the switching arrangement during any first phase are marked according to the cycle including this first phase and they are counted up as received during this first phase during all its duration. The counting means will not be detailed here, as they are also already known from the prior art.

10 After switching and before being transferred from the switching arrangement 1, the cells are counted again according to their respective marks corresponding to the checking cycle during which they were received. The output counting for each cycle is made during the second phase of the cycle for the cells containing the mark, which corresponds to the rank of the cycle in the series to  
15 which it belongs. As clearly understandable from figure 2, they are several countings simultaneously in progress for cells having different cycle marks during coexisting parts of second phases. This happens, for instance, when there are simultaneously a counting in progress during the second phase OC1 of cells marked according to cycle C1, a counting in progress during the second phase  
20 OC2 of cells marked according to cycle C2 and a counting in progress during the second phase OC3 of cells marked according to cycle C3, due to the fact that the checking cycles are interleaved.

A determination is made at the end of each second phase which corresponds to the end of the cycle including this second phase in order to point  
25 out if a correspondence otherwise determined between the input count and the output count for the cycle is obtained. Accordingly, the input and output counts for a cycle are found equal, if there is no duplication of cells specifically foreseen for at least one cell received during a first phase of a cycle, such as IC1 for cycle C1, and as long as there is no transfer error relating to the cells which were  
30 marked.

- 7 -

If as it happen that, for instance, there is an indication in the header of a cell pointing out that a multiplication, involving one or more copies, is requested at the level of the switching arrangement for further transfer of the cell to different destinations, the indication is processed as soon as received during a first phase of a cycle and one of the two countings made during this cycle is modified accordingly in order to have the intended correspondence obtained.

If corresponding input and output countings do not fit together, the result of the comparison is used in order to trigger a transfer error signaling from asynchronous switching arrangement 2 toward its supervision arrangement 5.

As long as the respective correspondences are as foreseen at the end of successive checking cycle, there is no need for transfer error signaling from the asynchronous switching arrangement.

In a preferred form, the input count during the first phase of a cycle is a count up realized in a dedicated counter and the output count during the following second phase of the cycle is a count down in the same counter, each cycle of a series having a dedicated counter according to its rank in the series. Accordingly, if there is no duplication of cells specifically foreseen among the cells received during a first phase, such as IC1 on figure 3, the end value obtained at the end of a cycle C must be zero if the sum value counted up of received cells at the end of the first phase corresponds exactly to the counted down value of transferred cells marked according to cycle C and obtained at the end of the second phase by which cycle C ends.

Taking into account requests for cell multiplication is easily obtained by an increase of the counting up or a decrease of the counting down as many times as they are copies of a cell which are requested. As exemplified on figure 3, the input count of received cells marked according to a cycle, such as C1, can increase only during all the first phase IC1 of this cycle. A decrease is possible as soon as the second phase OC1 starts. At the end of first phase IC1, during the rest of second phase OC2, the count can only decrease for cells marked according to C1. The checking at the end of the cycle is correct if a zero count is

- 8 -

obtained and then there is no specific error checking provided as long as a zero count is obtained at the end of the following checking cycles.

5 It must be also understood that the constitution of the input counting means 6 for a switching structure is dependent from the number "n" of data cell inputs of the switching structure as well as the constitution of the output counting means 7 is dependent from the number "m" of data cell outputs for this switching structure.

- 9 -

**CLAIMS**

1. Method for checking the transfer of data cells in an asynchronous switching arrangement (1) **characterized** in that it comprises a marking and a counting of the cells received and a counting of the cells, after switching when outputted from the switching structure (2) of the arrangement, in order to verify that the counts correspond and to find transfer errors of data cells due to unacceptable delays, loss and unwanted copying in the switching structure, said marking and counting being obtained according to a periodical time frame made of interleaved checking cycles which are grouped by limited and successive series of a same determined number of cycles, each cycle (C1) including a first phase (IC1) for marking and counting the cells as they are received, the identification mark, introduced in every cell received during this first phase, being related to the position of the cycle among the other cycles of the same series, with each first phase of a cycle following immediately the first phase of the preceding cycle, a second phase (OC1), starting with a determined delay (d1) after the beginning of the first phase of the same cycle, during and after this first phase for a determined duration (t2) and for counting the cells, as soon as switched, which contain the identification mark introduced during the first phase of the same checking cycle, a determination being made at the end of the second phase of each checking cycle of the correspondence between the two counts obtained during the cycle, with a specific signaling as soon as the correspondence as otherwise determined for a cycle is not obtained.

2. Method, according to claim 1, characterized in that the result of the counting of cells specifically marked according to a determined cycle relative to one series of cycles is obtained by a count down of cells, as soon as switched, during the second phase of said cycle from the instantaneous sum value counted up of cells as soon as received, which is obtained at any moment during of the first phase of the cycle, in order to obtain a zero value at the end of the said

- 10 -

second phase if the correspondence between counts, as otherwise determined for this cycle is verified.

5           **3.** Method according to anyone of claim 1 and claim 2, characterized in that one of the two countings made during a phase is modified as many times as they are copies of a received cell requested at the level of the switching arrangement.

10           **4.** Elementary asynchronous switching unit, **characterized** in that it comprises an asynchronous switching arrangement (1), including data cell transfer checking means for marking and counting the cells as soon as received and for counting the cells, as soon as switched, when outputted from the switching structure of the arrangement in order to verify that the counts correspond and to find transfer errors of data cells due to unacceptable delays  
15           and unwanted copying in the switching structure, said marking and said counting being obtained by marking (8) and counting (6, 7) means according to a periodical time frame obtained from timing means and made of interleaved checking cycles which are grouped by limited and successive series of a same determined number of cycles, each cycle (C1) including a first phase (IC1) for  
20           marking and counting the cells as soon as they are received, the identification mark, introduced in every cell received during this first phase, being related to the position of the cycle among the other cycles of the same series, with each first phase of a cycle following immediately the first phase of the preceding cycle, a second phase (OC1), starting with a determined delay (d1) after the beginning of  
25           the first phase of the same cycle and for a determined duration (t2) for counting the cells, as soon as switched, which contain the identification mark introduced during the first phase of the same checking cycle, a determination being made from the counting means at the end of the second phase of each checking cycle of the correspondence between the two counts made during the cycle with a  
30           specific signaling as soon as the correspondence otherwise determined for a cycle is not obtained.



- 11 -

5. Asynchronous switching network, according to claim 4, which includes inter-linked switching units in one or several asynchronous switching arrangements, characterized in that each asynchronous switching arrangement, comprises data cell transfer checking means for marking and counting the cells when received and for counting the cells, as soon as switched; when outputted from the switching structure of the arrangement in order to verify that the counts correspond and to find transfer errors of data cells due to unacceptable delays and unwanted copying in the switching structure, said marking and said counting being made by marking (8) and counting (6, 7) means according to a periodical time frame obtained from timing means and made of interleaved checking cycles which are grouped by limited and successive series of a same determined number of cycles, each cycle including a first phase for marking and counting the cells as soon as they are received, the identification mark, introduced in every cell received during this first phase, being related to the position of the cycle among the other cycles of the same series, with each first phase of a cycle following immediately the first phase of the preceding cycle, a second phase, starting with a determined delay, after the beginning of the first phase of the same cycle and during this first phase, for a determined duration and for counting the cells, as soon as switched, which contain the identification mark introduced during the first phase of the same checking cycle, a determination being made from the counting means at the end of the second phase of each checking cycle of the correspondence between the two counts during the cycle with a specific signaling as soon as the correspondence otherwise determined for a cycle is not obtained.

**THIS PAGE BLANK (USPTO)**

- 12 -

**ABSTRACT**

**METHOD FOR DETECTING LOSS OR EXCESSIVE DELAY IN THE  
TRANSFER OF DATA CELLS IN AN ASYNCHRONOUS SWITCHING  
ARRANGEMENT, ELEMENTARY SWITCHING UNIT AND NETWORK EQUIPPED  
FOR SUCH A METHOD**

5

For checking transfer of data cells in an asynchronous switching arrangement, cells are cyclically marked and counted before entering and after leaving the arrangement.

10

A periodical time frame composed of N interleaved checking cycles is imposed. Each cycle (C1) includes two phases, a first phase (IC1) for marking and counting the cells, when received and before switching, and a second counting phase (OC1) for counting cells after switching. An identification mark is introduced in every cell received during the first phase of every cycle, it is linked to the position of this cycle in the time frame. Cells marked according to a cycle are counted as soon as switched during the second phase of the cycle, which starts with a determined delay (d1) during each first phase, for a determined duration (t2). A determination of the correspondence between the two counts obtained during a cycle is made and induces a fault signaling as soon as such a correspondence as otherwise determined is not obtained.

20

Figure for publication: fig. 2

**THIS PAGE BLANK (USPTO)**

1/1

FIG. 1




FIG. 2





FIG. 3



**THIS PAGE BLANK (USPTO)**